

AQUASOFT VELOURS

Waterborne interior alkyd paint - Velvet



PRODUCT OVERVIEW

New and maintenance work for walls and ceilings in dry and wet rooms with ventilation Recommended for surfaces with a pH lower than 9

BENEFITS

Excellent wet scrub resistance (Class 1 according to NF EN 13300)
 Good water vapour permeability
 Very low yellowing in the dark
 High hiding power
 Fast drying
 Odourless
 Odourless
 Certified NF Environment and label EXCELL ZONE VERTE

TECHNICAL SPECIFICATIONS

CERTIFICATIONS	 
FINISH	silky satin smooth
DENSITY	1.43 +/- 0,05 Kg/l
SOLIDS BY	Weight : 56 +/- 2% Volume : 41 +/- 2%
VOC	EU limit value for this product . (cat. A/a): 30 g/l (2010). This product contains max 10 g/l VOC
GLOSS LEVEL AT	12 ± 2 % 85°
AFNOR CLASSIFICATION NFT 36 005	Rating Family I Class 4a/7b2
COLOURS	White, pastel, medium and deep tints from the Peintures Maestria Colour chart
CONTAINER SIZE	1L - 2.5L - 15L

SURFACE PREPARATION | APPLICATION

As stated by DTU 59.1, all surfaces must be clean, dry and free of dirt.

For new work, all surfaces must be primed with an appropriate primer.

Old glossy painted surfaces should be sanded or washed with a cleaner and then rinsed with water.

For deep tones such as yellow or red, apply one coat of primer grey for a better opacity. These recommendations do not override a specific description of the substrate.

Application conditions	DTU 59.1
Application equipment	Brush : Dilution Ready to use Roller : Dilution Ready to use Airless spray-gun : Dilution Ready to use.
Practical coverage	10 to 12 m ² /l per coat depending on surface texture.
Thinner / Clean-up solvent	Water
Drying time (20°C -65% RH)	Dust free : 1 h Dry : 2 h Recoat : 8 to 10 h

AQUASOFT VELOURS

SYSTEM RECOMMENDATIONS

Substrate	wood and wood joinery, hydraulic binder-based coating, plasterboard, previously painted surfaces in good condition	plaster
Primer coat	Apply 1 coat of PRIM O 2010 or IKARPRIM	Apply 1 coat of IKARPRIM or IKARFIX O
Top coat		Apply 2 coats of AQUASOFT VELOURS

SAFETY MEASURES

Storage	Can be kept for 1 year in unopened original container. Protect from freezing and high temperatures.
Précaution d emploi	Shake or stir before use. Use in well-ventilated areas. Keep out of reach of children. For personal protection, refer to the Safety Data Sheet (SDS).
Transport	Not subject to ADR regulations (European Agreement concerning the International Carriage of Dangerous Goods by Road).
Gestion des déchets	Close the container tightly after use. Do not dispose of residues in the sewer or with household waste. Please take your empty container to an approved collection center. Contact local authorities for information on disposal and collection procedures.