

AQUASTRIA PRIMER

Waterborne interior alkyd primer



PRODUCT OVERVIEW

Universal primer for a wide variety of substrates Ideal for achieving a perfect finish

BENEFITS

Excellent adhesion
High hiding power
Microporous
Odourless

TECHNICAL SPECIFICATIONS

| | |
|---------------------------------|--|
| FINISH | flat |
| DENSITY | 1.49 +/- 0,05 Kg/l |
| SOLIDS BY | Weight : 60 +/- 2% Volume : 40 +/- 2% |
| VOC | EU limit value for this product . (cat. A/g): 30 g/l (2010). This product contains max 30 g/IVOC |
| FLASH POINT | Not applicable |
| GLOSS LEVEL AT | 10% 60° |
| AFNOR CLASSIFICATION NFT 36 005 | Rating Family I Class 7b2 |
| COLOURS | White |
| CONTAINER SIZE | 5L - 15L |

SURFACE PREPARATION | APPLICATION

As stated by DTU 59.1, all surfaces must be clean, dry and free of dirt.

For maintenance work, remove peeling paint by brushing, scraping or sanding. Old glossy painted surfaces must be sanded or washed with an appropriate cleaner and then rinsed with water.

In the presence of contaminants such as mildew, molds or bacteria, apply an anti-fungal treatment named IKAR AM. These recommendations do not override a specific description of the substrate.

| | |
|-----------------------------------|--|
| Application conditions | DTU 59.1 |
| Application equipment | Brush : Dilution Ready to use Roller : Dilution Ready to use. |
| Practical coverage | 8 to 10 m ² /l per coat depending on surface texture. |
| Thinner / Clean-up solvent | Water |
| Drying time (20°C -65% RH) | Dry : 1 to 2 h Recoat : 6 h |

AQUASTRIA PRIMER

SYSTEM RECOMMENDATIONS

| | | |
|--------------------|--|--------------------------|
| Substrate | wood and wood joinery, hydraulic binder-based coating, plasterboard | plaster |
| Primer coat | Apply 1 coat of AQUASTRIA PRIMER | Apply 1 coat of IKARPRIM |
| Top coat | Apply 1 or 2 coats of waterborne alkyd or acrylic paint | |

SAFETY MEASURES

| | |
|----------------------------|---|
| Storage | Can be kept for 1 year in unopened original container. Protect from freezing and high temperatures. |
| Précaution d emploi | Shake or stir before use. Use in well-ventilated areas. Keep out of reach of children. For personal protection, refer to the Safety Data Sheet (SDS). |
| Transport | Not subject to ADR regulations (European Agreement concerning the International Carriage of Dangerous Goods by Road). |
| Gestion des déchets | Close the container tightly after use. Do not dispose of residues in the sewer or with household waste. Please take your empty container to an approved collection center. Contact local authorities for information on disposal and collection procedures. |