

AQUASTRIA VELOURS

Waterborne interior acrylic paint - Velvet



PRODUCT OVERVIEW

New and maintenance work for interior walls in dry rooms
Commercial and residential sites

BENEFITS

High hiding power
No yellowing (even in dark rooms)
Wet scrub resistance (class 2 according to NF EN 13300)
Quick drying
Washable

AFNOR Classification NFT 36 005 Rating Family I Class 7b2

TECHNICAL SPECIFICATIONS

Finish	: silky satin smooth
Density	: 1.37 +/- 0,05 Kg/l
Solids by	: Weight: 60 +/- 2% Volume: 43 +/- 2%
VOC (directive 2004/42/CE)	: EU limit value for this product . (cat. A/a): 30 g/l (2010). This product contains max 15 g/IVOC
Flash point	: Not applicable
Gloss level at to 85°	: 10 - 15 %
Practical coverage	: 9 to 10 m²/l per coat depending on surface texture.
Drying time (20°C -65% RH)	: Dry : 2 h Recoat : 6 h
Colours	: White, medium and deep tints from the Peintures Maestria colour chart
Storage	: Can be kept for 1 year in unopened original container. Protect from freezing and high temperatures.

AQUASTRIA VELOURS

Waterborne interior acrylic paint - Velvet



SURFACE PREPARATION

As stated by DTU 59.1, all surfaces must be clean, dry and free of dirt.

Old glossy painted surfaces must be previously sanded or washed with an appropriate cleaner and then rinsed with water.

In the presence of contaminants such as mildew, molds or bacteria, apply an anti-fungal treatment named IKAR AM.

These recommendations do not override a specific description of the substrate.

APPLICATION

Application conditions	: DTU 59.1
Application equipment	: Brush, Roller, Enamel roller. Airless spray-gun.
Clean-up solvent	: Water
Thinner	: Water
Dilution	: Brush (Ready to use), Roller (Ready to use), Enamel roller (5 to 10 %). Airless spray-gun (15 to 20 %).

SYSTEM RECOMMENDATIONS

Substrate	Primer coat	Top coat
hydraulic binder-baser coatings, plasterboard, previously painted surfaces in good conditions	Apply 1 coat of PRIM O 2010	Apply 2 coats of AQUASTRIA VELOURS
plaster	Apply 1 coat of IKARPRIM	

CONTAINER SIZE

1L - 2.5L - 5L - 15L

SAFETY MEASURES

Refer to the Safety Data Sheet