

DECONATURE MAT

Waterborne interior acrylic paint - Flat





PRODUCT OVERVIEW

New and maintenance work Excellent top coat for interior walls and ceilings in dry rooms Ideal for HQE projects (French certification)

BENEFITS

Odourless
Excellent covering
No yellowing
Quick drying
Washable
Certified EUROPEAN ECOLABEL
Contains an anti-rust additive
Good wet scrub resistance (Class 2 according to NF EN 13300)

TECHNICAL SPECIFICATIONS

CERTIFICATIONS	  EU ECOLABEL : FR/044/014
FINISH	flat
DENSITY	1.52 +/- 0,05 Kg/l
SOLIDS BY	Weight : 66 +/- 2% Volume : 48 +/- 2%
VOC	EU limit value for this product . (cat. A/a): 30 g/l (2010). This product contains max 1 g/IVOC
FLASH POINT	Not applicable
GLOSS LEVEL AT	approximately 4% 85°
AFNOR CLASSIFICATION NFT 36 005	Rating Family I Class 7b2
COLOURS	White, medium and deep tints from the Peintures Maestria colour chart
CONTAINER SIZE	2.5L - 15L

SURFACE PREPARATION | APPLICATION

As stated by DTU 59.1, all surfaces must be clean, dry and free of dirt.
Old glossy painted surfaces must be previously sanded or washed with an appropriate cleaner and then rinsed with water.
Must be applied on coherent and porous substrates.
Unpainted surfaces must be previously primed.
Lime based coating must be removed with an appropriate cleaner and then rinsed with water.
These recommendations do not override a specific description of the substrate.

Application conditions	DTU 59.1
Application equipment	Brush : Dilution Ready to use Roller : Dilution Ready to use Airless spray-gun : Dilution 5 to 10 %.
Practical coverage	9 to 11 m ² /l per coat depending on surface texture.
Thinner / Clean-up solvent	Water
Drying time (20°C -65% RH)	Dust free : 30 mn Dry : 2 h Recoat : 6 h

DECONATURE MAT

SYSTEM RECOMMENDATIONS

Substrate	plaster	plasterboard, cement, previously painted surfaces in good condition
Primer coat	Apply 1 coat of IKARPRIM	Apply 1 coat of DECONATURE IMPRESSION, PRIM 0 2010 or AQUASTRIA PRIMER.
Top coat	Apply 2 coats of DECONATURE MAT	

SAFETY MEASURES

Storage	Can be kept for 1 year in unopened original container. Protect from freezing and high temperatures.
Précaution d emploi	Shake or stir before use. Use in well-ventilated areas. Keep out of reach of children. For personal protection, refer to the Safety Data Sheet (SDS).
Transport	Not subject to ADR regulations (European Agreement concerning the International Carriage of Dangerous Goods by Road).
Gestion des déchets	Close the container tightly after use. Do not dispose of residues in the sewer or with household waste. Please take your empty container to an approved collection center. Contact local authorities for information on disposal and collection procedures.