

DECOPUR VELOURS

Waterborne depolluting paint - Velvet




PRODUCT OVERVIEW

New and maintenance work Residential and commercial sites
Top coat for interior walls in dry rooms Ideal for schools, retirement homes, nurseries...

BENEFITS

Odourless
Quick drying
Depolluting by elimination of formaldehyde molecules
Excellent wet scrub resistance (Class 1 according to NF EN 13300)
Certified European Ecolabel (VOC 1 g/l)
No yellowing (even in the dark)

TECHNICAL SPECIFICATIONS

CERTIFICATIONS	 EU ECOLABEL : FR/044/014
DENSITY	1.44 +/- 0,05 Kg/l
SOLIDS BY	Weight : 60 +/- 2% Volume : 42 +/- 2%
VOC	EU limit value for this product . (cat. A/a): 30 g/l (2010). This product contains max 1 g/IVOC
GLOSS LEVEL AT	10 +/- 5 % 60°
AFNOR CLASSIFICATION NFT 36 005	Rating Family I Class 7b2
COLOURS	White, medium and deep tints from the Peintures Maestria colour chart
CONTAINER SIZE	5L, 15L

SURFACE PREPARATION | APPLICATION

As stated by DTU 59.1, all surfaces must be clean, dry and free of dirt.
Old glossy painted surfaces must be previously sanded or washed with an appropriate cleaner and then rinsed with water.
Must be applied on coherent and porous substrates.
Unpainted surfaces must be previously primed. These recommendations do not override a specific description of the substrate.

Application conditions	DTU 59.1
Application equipment	Brush : Dilution Ready to use Roller : Dilution Ready to use Airless spray-gun : Dilution 0 to 5 %.
Practical coverage	9 to 11 m²/l per coat depending on surface texture.
Thinner / Clean-up solvent	Water
Drying time (20°C -65% RH)	Dry : 2 h Recoat : 8 h

DECOPUR VELOURS

SYSTEM RECOMMENDATIONS

Substrate	plaster	concrete, plasterboard, cement, hydraulic binder-based coating, previously painted surfaces in good condition
Primer coat	Apply 1 coat of IKARPRIM	Apply 1 coat of PRIM O 2010 or AQUASTRIA PRIMER or DECONATURE IMPRESSION
Top coat	Apply 2 coats of DECOPUR VELOURS	

SAFETY MEASURES

Storage	Can be kept for 1 year in unopened original container. Protect from freezing and high temperatures.
Précaution d emploi	Shake or stir before use. Use in well-ventilated areas. Keep out of reach of children. For personal protection, refer to the Safety Data Sheet (SDS).
Transport	Not subject to ADR regulations (European Agreement concerning the International Carriage of Dangerous Goods by Road).
Gestion des déchets	Close the container tightly after use. Do not dispose of residues in the sewer or with household waste. Please take your empty container to an approved collection center. Contact local authorities for information on disposal and collection procedures.