

# FLEXIKAR INTER

Waterborne exterior elastomeric coating



## PRODUCT OVERVIEW

New and maintenance work Residential and commercial sites  
Recommended for a wide variety of exterior masonry projects  
Ideal for vertical walls with cracks (from 0 to 2.0 mm)

## TECHNICAL SPECIFICATIONS

DENSITY	1.28 +/- 0,05 Kg/l
SOLIDS BY	Weight : 63 +/- 2%
AFNOR CLASSIFICATION NFT 36 005	Rating Family II Class 2b/1b
COLOURS	White
CONTAINER SIZE	15L

## BENEFITS

Excellent crack resistance (from 0 to 2.0 mm)  
Good adhesion  
Microporous  
French classification A2 to A5 - Standard P84.403  
European classification G3E4S1V2W2A2C0 to G3E5S1V2W2A5C0  
- Standard EN 1062-1

## SURFACE PREPARATION | APPLICATION

As stated by DTU 42.1, all surfaces must be clean, dry and free of dirt.  
Old glossy painted surfaces must be previously sanded or washed with an appropriate cleaner and then rinsed with water.  
In the presence of contaminants such as mildew, molds or bacteria, apply an anti-fungal treatment named IKAR BACTERICIDE.  
If required a high-pressure cleaning must be carried out, followed by the application of an anti-fungal treatment named IKAR BACTERICIDE.  
Unpainted surfaces must be primed with a suitable primer. These recommendations do not override a specific description of the substrate.

<b>Application conditions</b>	DTU 42.1
<b>Application equipment</b>	Facade roller : Dilution Ready to use.
<b>Practical coverage</b>	250 to 800 gr/m <sup>2</sup> per coat depending on surface texture.
<b>Thinner / Clean-up solvent</b>	Water
<b>Drying time (20°C -65% RH)</b>	Dry : 12 h Recoat : 24 h

## FLEXIKAR INTER

### SYSTEM RECOMMENDATIONS

<b>Substrate</b>	<b>concrete, cement, hydraulic binder-based coating</b>	<b>plaster, lime based coating</b>	<b>previously painted surfaces in good condition</b>
<b>Primer coat</b>	Apply 1 coat of IKARFIX O or IKARFIX S or IKARFIX IP	Apply 1 coat of IKARFIX S	Apply 1 coat of IKARFIX O
<b>Top coat</b>	Apply 1 coat of FLEXIKAR INTER NOTE: refer to Technical Data Sheet of FLEXIKAR TALOCHE for the consumption		

### SAFETY MEASURES

<b>Storage</b>	Can be kept for 1 year in unopened original container. Protect from freezing and high temperatures.
<b>Précaution d emploi</b>	Shake or stir before use. Use in well-ventilated areas. Keep out of reach of children. For personal protection, refer to the Safety Data Sheet (SDS).
<b>Transport</b>	Not subject to ADR regulations (European Agreement concerning the International Carriage of Dangerous Goods by Road).
<b>Gestion des déchets</b>	Close the container tightly after use. Do not dispose of residues in the sewer or with household waste. Please take your empty container to an approved collection center. Contact local authorities for information on disposal and collection procedures.