

IKARBOIS

Solventborne interior & exterior wood stain



PRODUCT OVERVIEW

New and maintenance work
Impregnation wood stain (colourless or pigmented)
Excellent decoration and protection for wood and wood joinery

BENEFITS

Great water repellency
Excellent UV and weather resistance
Microporous

AFNOR Classification NFT 36 005 Rating Family I Class 4a

TECHNICAL SPECIFICATIONS

Finish	: satin
Density	: 0.84 +/- 0,05 Kg/l
Solids by	: Weight: 27 +/- 2% Volume: 22 +/- 2%
VOC (directive 2004/42/CE)	: EU limit value for this product . (cat. A/f): 700 g/l (2010). This product contains max 650 g/IVOC
Flash point	: 23°C to 55°C
Practical coverage	: 8 to 16 m²/l per coat depending on surface texture.
Drying time (20°C -65% RH)	: Dry : 24 to 48 h Recoat : 24 to 48 h depending on wood specie
Colours	: IKARBOIS colour chart
Storage	: Can be kept for 1 year in unopened original container. Protect from freezing and high temperatures.

IKARBOIS

Solventborne interior & exterior wood stain



SURFACE PREPARATION

As stated by DTU 59.1, all surfaces must be clean, dry and free of dirt.

For maintenance work, remove peeling paint by brushing, scraping or sanding. Old glossy painted surfaces must be sanded or washed with an appropriate cleaner and then rinsed with water.

If necessary, substrates must first be treated with a fungal treatment.

NOTE: Tints give variable results depending on wood specie. A preliminary adherence test must be carried out.

These recommendations do not override a specific description of the substrate.

APPLICATION

Application conditions	: DTU 59.1
Application equipment	: Brush, Airless spray-gun.Dipping.
Clean-up solvent	: White spirit
Thinner	: White spirit
Dilution	: Brush (Ready to use), Airless spray-gun (Ready to use).Dipping (Ready to use).

SYSTEM RECOMMENDATIONS

Substrate	Primer coat	Top coat
wood and wood joinery, stripped wood	Apply 1 coat of IKARBOIS	exterior: Apply 2 coats of IKARBOIS SATIN THIXO interior: Apply 1 coat of IKARBOIS SATIN THIXO
anti-drying wood such as Iroko	Apply 1 coat of suitable primer	

CONTAINER SIZE

1L - 5L

SAFETY MEASURES

Refer to the Safety Data Sheet