

# IKARFIX O

Waterborne interior & exterior acrylic paint



## PRODUCT OVERVIEW

New and maintenance work  
Commercial and residential sites in dry and wet rooms

## BENEFITS

Excellent adhesion  
Good alkali resistance  
Great hiding power  
Microporous

AFNOR Classification NFT 36 005 Rating Family I Class 7b2

## TECHNICAL SPECIFICATIONS

<b>Density</b>	: 1.54 +/- 0,05 Kg/l	
<b>Solids by</b>	: Weight: 68 +/- 2%	Volume: 50 +/- 2%
<b>VOC (directive 2004/42/CE)</b>	: EU limit value for this product . (cat. A/h): 30 g/l (2010).	This product contains max 30 g/lVOC
<b>Flash point</b>	: Not applicable	
<b>Practical coverage</b>	: 150 to 200 gr/m <sup>2</sup>	per coat depending on surface texture.
<b>Drying time (20°C -65% RH)</b>	: Dry : 1 h	Recoat : 12 h
<b>Colours</b>	: White	
<b>Storage</b>	: Can be kept for 1 year in unopened original container.	Protect from freezing and high temperatures.

## IKARFIX O

Waterborne interior & exterior acrylic paint



### SURFACE PREPARATION

As stated by DTU 59.1, all surfaces must be clean, dry and free of dirt.

Interior: Old glossy painted surfaces must be previously sanded or washed with an appropriate cleaner and then rinsed with water.

In the presence of contaminants such as mildew, molds or bacteria, apply an anti-fungal treatment named IKAR AM.

Exterior: if required a high-pressure cleaning must be carried out, followed by the application of an anti-fungal treatment named IKAR AM.

For powdery surface, apply 1 coat of IKARFIX S.

These recommendations do not override a specific description of the substrate.

### APPLICATION

<b>Application conditions</b>	: DTU 59.1
<b>Application equipment</b>	: Brush, Facade roller.
<b>Clean-up solvent</b>	: Water
<b>Thinner</b>	: Water
<b>Dilution</b>	: Brush (Ready to use), Facade roller (Ready to use).

### SYSTEM RECOMMENDATIONS

Substrate	Primer coat	Top coat
concrete, cement, hydraulic binder-based coating	Apply 1 coat of IKARFIX O	Apply 1 or 2 coats of interior or exterior paints

### CONTAINER SIZE

7Kg / 20Kg

### SAFETY MEASURES

Refer to the Safety Data Sheet