

# IKARPRIM

Solventborne interior alkyd primer



## PRODUCT OVERVIEW

Universal primer for a wide variety of substrates  
Recommended for slightly brittle surface

## BENEFITS

Highly penetrating paint  
Good sealing properties  
Great water repellency

AFNOR Classification NFT 36 005 Rating Family I Class 4a

## TECHNICAL SPECIFICATIONS

<b>Finish</b>	: flat
<b>Density</b>	: 1.49 +/- 0,05 Kg/l
<b>Solids by</b>	: Weight: 79 +/- 2%      Volume: 60 +/- 2%
<b>VOC (directive 2004/42/CE)</b>	: EU limit value for this product (cat. A/g): 450 g/l (2007),. (cat. A/g): 350 g/l (2010). This product contains max 350 g/IVOC
<b>Flash point</b>	: 23°C to 55°C
<b>Practical coverage</b>	: 10 to 13 m²/l per coat depending on surface texture.
<b>Drying time (20°C -65% RH)</b>	: Dry : 4 h Recoat : 24 h
<b>Colours</b>	: White
<b>Storage</b>	: Can be kept for 1 year in unopened original container. Protect from freezing and high temperatures.

## IKARPRIM

Solventborne interior alkyd primer



### SURFACE PREPARATION

As stated by DTU 59.1, all surfaces must be clean, dry and free of dirt.

Old glossy painted surfaces must be previously sanded or washed with an appropriate cleaner and then rinsed with water.

In the presence of contaminants such as mildew, molds or bacteria, apply an anti-fungal treatment named IKAR BACTERICIDE.

These recommendations do not override a specific description of the substrate.

### APPLICATION

<b>Application conditions</b>	: DTU 59.1
<b>Application equipment</b>	: Brush, Roller.
<b>Clean-up solvent</b>	: White spirit
<b>Thinner</b>	: White spirit
<b>Dilution</b>	: Brush (0 to 5 %), Roller (0 to 5 %).

### SYSTEM RECOMMENDATIONS

Substrate	Primer coat	Top coat
wood and wood joinery, plaster and plaster derivatives, previously painted surfaces in good condition	Apply 1 coat of IKARPRIM	Apply 1 or 2 coats of waterborne acrylic or alkyd paint

### CONTAINER SIZE

0.5L - 2.5L - 15L

### SAFETY MEASURES

Refer to the Safety Data Sheet