

IKARTOILE

Reinforcement fabric

PRODUCT OVERVIEW

Nonwoven polyester reinforcement fabric.

BENEFITS

Excellent resistance to moisture and wear.
Excellent air permeability.

IKARTOILE is available in two types :

- IKARTOILE 94-30 D
- IKARTOILE 94-50 S

IKARTOILE is packaged in 50 metre rolls of several widths :

- IKARTOILE 94-30 D : 50 x 0,14 m and 50 x 1 m
- IKARTOILE 94-50 S : 50 x 0,15 m, 50 x 0,35 m and 50 x 1 m

To keep away from moisture.

AFNOR Classification NFT 36 005 Rating Family I Class 7b2/10c

TECHNICAL SPECIFICATIONS

IKARTOILE

Reinforcement fabric

SURFACE PREPARATION

The fabric must be unrolled only as fast as it is applied to the prepared, primed substrate. It must be sunk into the first coat of the system.

IKARTOILE 94-30 D : designed for use on flat base sheets in façade waterproofing systems. The fabric becomes totally invisible in the coating. Use as a braid to bridge joints and cracks.

Weight : 30 g/m²

Gauge : 0,12 mm

Fringed : no

IKARTOILE 94-50 S : the flexible fabric hugs irregular surfaces so it is ideal for :

- waterproofing on façades with salient features (parapets, bands, cornice mouldings, etc...).
- base sheets and flashing in roofing, terraces, etc...

Weight : 50 g/m²

Gauge : 0,60 mm

Fringed : 2 edges

These recommendations do not override a specific description of the substrate.

APPLICATION

SYSTEM RECOMMENDATIONS

CONTAINER SIZE

SAFETY MEASURES

Refer to the product's MSDS