

# IKARWOOD SATIN

Solventborne interior & exterior alkyd paint - Satin



## PRODUCT OVERVIEW

New and maintenance work  
Can be used as primer and top coat  
Ideal for use on properly prepared wood and wood joinery  
Specially recommended for exterior use

## BENEFITS

Microporous  
Great hardness  
High block resistance

AFNOR Classification NFT 36 005 Rating Family I Class 4a

## TECHNICAL SPECIFICATIONS

<b>Finish</b>	: satin
<b>Density</b>	: 1.37 +/- 0,05 Kg/l
<b>Solids by</b>	: Weight: 73 +/- 2%      Volume: 55 +/- 2%
<b>VOC (directive 2004/42/CE)</b>	: EU limit value for this product . (cat. A/d): 300 g/l (2010). This product contains max 300 g/IVOC
<b>Flash point</b>	: 23°C to 55°C
<b>Gloss level at to 60°</b>	: 35
<b>Practical coverage</b>	: 9 to 13 m²/l per coat depending on surface texture.
<b>Drying time (20°C -65% RH)</b>	: Dry : 8 to 10 h Recoat : 24 h
<b>Colours</b>	: White, medium and depp tints from the Peintures Maestria colour chart
<b>Storage</b>	: Can be kept for 1 year in unopened original container. Protect from freezing and high temperatures.

## IKARWOOD SATIN

Solventborne interior & exterior alkyd paint - Satin



### SURFACE PREPARATION

As stated by DTU 59.1, all surfaces must be clean, dry and free of dirt.

For maintenance work, remove peeling paint by brushing, scraping or sanding. Old glossy painted surfaces must be sanded or washed with an appropriate cleaner and then rinsed with water.

If necessary, substrates must first be treated with a fungal treatment.

These recommendations do not override a specific description of the substrate.

### APPLICATION

<b>Application conditions</b>	: DTU 59.1
<b>Application equipment</b>	: Brush, Roller, Airless spray-gun.
<b>Clean-up solvent</b>	: White spirit
<b>Thinner</b>	: White spirit
<b>Dilution</b>	: Brush (Ready to use), Roller (Ready to use), Airless spray-gun (Ready to use).

### SYSTEM RECOMMENDATIONS

Substrate	Primer coat	Top coat
wood and wood joinery, previously painted surfaces in good condition		Interior : Apply 1 or 2 coats of IKARWOOD SATIN Exterior : Apply 2 coats of IKARWOOD SATIN
new or stripped wood	Apply 1 coat of IKARWOOD SATIN diluted with 10 % of White Spirit	

### CONTAINER SIZE

0.5L - 2.5L - 10L

### SAFETY MEASURES

Refer to the Safety Data Sheet