



IMPRESSION PLACO

Waterborne interior acrylic primer



PRODUCT OVERVIEW

New and maintenance work Primer for low porosity surfaces in good condition Ideal for HQE projects

BENEFITS

Odourless High hiding power Good adhesion Great sealing properties Certified EUROPEAN ECOLABEL

CERTIFICATIONS	EU ECOLABEL : FR/044/014
FINISH	flat
DENSITY	1.67 +/- 0,05 Kg/l
SOLIDS BY	Weight : 68 +/- 2% Volume : 47 +/- 2%
VOC	EU limit value for this product . (cat. A/g): 30 g/l (2010). This product contains max 10 g/IVOC
FLASH POINT	Not applicable
GLOSS LEVEL AT	10 % 60°
AFNOR CLASSIFICATION NFT 36 005	Rating Family I Class 7b2
COLOURS	White
CONTAINER SIZE	15L

TECHNICAL SPECIFICATIONS

SURFACE PREPARATION | APPLICATION

As stated by DTU 59.1, all surfaces must be clean, dry and free of dirt.

For maintenance work, remove peeling paint by brushing, scraping or sanding. Old glossy painted surfaces must be sanded or washed with an appropriate cleaner and then rinsed with water.
In the presence of contaminants such as mildew, molds or bacteria, apply an anti-fungal treatment named IKAR BACTERICIDE. These recommendations

do not override a specific description of the substrate.

Application conditions	DTU 59.1
Application equipment	Brush : Dilution 5 to 10 % Roller : Dilution 5 to 10 % Airless spray-gun : Dilution 5 to 10 %.
Practical coverage	5 to 10 m²/l per coat depending on surface texture.
Thinner / Clean-up solvent	Water
Drying time (20°C -65% RH)	Dust free : 20 mn Dry : 1 h Recoat : 2 h





IMPRESSION PLACO

			DATI	

Substrate	plasterboard, concrete, hydraulic binder-based coating, unstained surfaces in good condition	stained surfaces	plaster	
Primer coat	Apply 1 coat of IMPRESSION PLACO	Apply 1 coat of NORWAY or IKARPRIM	Apply 1 coat of IKARPRIM	
Top coat	Apply 1 or 2 coats of waterborne alkyd or acrylic paint			

SAFETY MEASURES

Storage	Can be kept for 1 year in unopened original container. Protect from freezing and high temperatures.
Précaution d emploi	Shake or stir before use. Use in well-ventilated areas. Keep out of reach of children. For personal protection, refer to the Safety Data Sheet (SDS).
Transport	Not subject to ADR regulations (European Agreement concerning the International Carriage of Dangerous Goods by Road).
Gestion des déchets	Close the container tightly after use. Do not dispose of residues in the sewer or with household waste. Please take your empty container to an approved collection center. Contact local authorities for information on disposal and collection procedures.

ISO 9001 ISO 14001 BUREAU VERITAS