

KATEX

Waterborne interior & exterior acrylic paint



PRODUCT OVERVIEW

New and maintenance work Ideal for large surfaces in good condition Interior: only dry rooms

BENEFITS

High hiding power
Good adhesion
Good alkali resistance
Microporous
Wet scrub resistance (Class 3 according to NF EN 13300)

TECHNICAL SPECIFICATIONS

FINISH	flat
DENSITY	1.65 +/- 0,05 Kg/l
SOLIDS BY	Weight : 66 +/- 2% Volume : 44 +/- 2%
VOC	EU limit value for this product (cat. A/a): 75 g/l (2007),.. (cat. A/a): 30 g/l (2010). This product contains max 30 g/IVOC
FLASH POINT	Not applicable
GLOSS LEVEL AT	5 % 60°
AFNOR CLASSIFICATION NFT 36 005	Rating Family I Class 7b2
COLOURS	White and pastel tints from the Peintures Maestria colour chart
CONTAINER SIZE	2.5L - 15L

SURFACE PREPARATION | APPLICATION

As stated by DTU 59.1, all surfaces must be clean, dry and free of dirt.
Interior: Old glossy painted surfaces must be previously sanded or washed with an appropriate cleaner and then rinsed with water.
In the presence of contaminants such as mildew, molds or bacteria, apply an anti-fungal treatment named IKAR AM.
Exterior: if required an high-pressure cleaning must be carried out, followed by the application of an anti-fungal treatment named IKAR AM.
These recommendations do not override a specific description of the substrate.

Application conditions	DTU 59.1
Application equipment	Brush : Dilution 0 to 5 % Roller : Dilution 0 to 5 % Facade roller : Dilution 0 to 5 % Airless spray-gun : Dilution 0 to 5 %.
Practical coverage	5 to 10 m²/l per coat depending on surface texture.
Thinner / Clean-up solvent	Water
Drying time (20°C -65% RH)	Dust free : 20 mn Dry : 1 h Recoat : 2 h



KATEX

SYSTEM RECOMMENDATIONS

Substrate	exterior: concrete, hydraulic binder-based coating	interior: concrete, hydraulic binder-based coating, previously painted surfaces in good condition	interior: previously painted weatherboarding, old galvanised weatherboarding
Primer coat	Apply 1 coat of IKARFIX S or IKARFIX O or IKARFIX IP	Apply 1 coat of IMPRESSION PLACO or PRIM O 2010 or AQUASTRIA PRIMER	Apply 1 coat of a suitable primer
Top coat	Apply 2 coats of KATEX		

SAFETY MEASURES

Storage	Can be kept for 1 year in unopened original container. Protect from freezing and high temperatures.
Précaution d emploi	Shake or stir before use. Use in well-ventilated areas. Keep out of reach of children. For personal protection, refer to the Safety Data Sheet (SDS).
Transport	Not subject to ADR regulations (European Agreement concerning the International Carriage of Dangerous Goods by Road).
Gestion des déchets	Close the container tightly after use. Do not dispose of residues in the sewer or with household waste. Please take your empty container to an approved collection center. Contact local authorities for information on disposal and collection procedures.