

MULTIWAY

Waterborne interior & exterior acrylic paint - Velvet



PRODUCT OVERVIEW

New and maintenance work
Multi-surface paint for interior and exterior
Perfect adhesion to a wide range of substrates (VOC < 5 g/l)

BENEFITS

Good alkali resistance
Excellent adhesion
Great UV resistance
High wet scrub resistance (Class 1 according to NF EN 13300)
Contains an anti-rust additive

AFNOR Classification NFT 36 005 Rating Family I Class 7b2

TECHNICAL SPECIFICATIONS

Finish	: silky satin
Density	: 1.33 +/- 0,05 Kg/l
Solids by	: Weight: 57 +/- 2% Volume: 43 +/- 2%
VOC (directive 2004/42/CE)	: EU limit value for this product (cat. A/a): 75 g/l (2007),. (cat. A/a): 30 g/l (2010). This product contains max 5 g/lVOC
Flash point	: Not applicable
Gloss level at to 85°	: 8-12 %
Practical coverage	: 5 to 10 m²/l per coat depending on surface texture.
Drying time (20°C -65% RH)	: Dry : 4 h Recoat : 6 h 5 to 6 m²/l for outdoors - 9 to 10 m²/l for indoors
Colours	: White, medium and deep tints from the Peintures Maestria colour chart
Storage	: Can be kept for 1 year in unopened original container. Protect from freezing and high temperatures.

MULTIWAY

Waterborne interior & exterior acrylic paint - Velvet



SURFACE PREPARATION

As stated by DTU 59.1, all surfaces must be clean, dry and free of dirt.

Interior: Old glossy painted surfaces must be previously sanded or washed with an appropriate cleaner and then rinsed with water.

In the presence of contaminants such as mildew, molds or bacteria, apply an anti-fungal treatment named IKAR AM.

Exterior: if required an high-pressure cleaning must be carried out, followed by the application of an anti-fungal treatment named IKAR AM.

Unpainted metals should be sanded and the grease removed using a non-greasy solvent beforehand before priming.

These recommendations do not override a specific description of the substrate.

APPLICATION

Application conditions	: DTU 59.1
Application equipment	: Brush, Roller, Facade roller, Airless spray-gun.
Clean-up solvent	: Water
Thinner	: Water
Dilution	: Brush (Ready to use), Roller (0 to 5 %), Facade roller (0 to 5 %), Airless spray-gun (3 to 5 %).

SYSTEM RECOMMENDATIONS

Substrate	Primer coat	Top coat
interior & exterior: concrete, hydraulic binder-based coating, cement, stripped galvanised metals, PVC, previously painted surfaces in good condition	Apply 1 coat of MULTIWAY diluted to 5 %	Apply 2 coats of MULTIWAY
interior: plasterboard, porous concrete, protected ferrous metals	Apply 1 coat of MULTIWAY diluted to 5 %	
interior: wood joinery with a risk of tannin staining	Apply 1 coat of NORWAY	
plaster	Apply 1 coat of IKARPRIM	

CONTAINER SIZE

2.5L - 15L

SAFETY MEASURES

Refer to the Safety Data Sheet