



OLEOMAT

Waterborne lime-based ceiling paint



PRODUCT OVERVIEW

New and maintenance work Only used in dry rooms Ideal for HQE projects

TECHNICAL SPECIFICATIONS

CERTIFICATIONS	 <small>EU ECOLABEL : FR/044/014</small>
FINISH	flat
DENSITY	1.50 +/- 0,05 Kg/l
SOLIDS BY	Weight : 60 +/- 2% Volume : 40 +/- 2%
VOC	EU limit value for this product . (cat. A/a): 30 g/l (2010). This product contains max 10 g/l VOC
FLASH POINT	Not applicable
GLOSS LEVEL AT	1,5 % 85°
AFNOR CLASSIFICATION NFT 36 005	Rating Family I Class 2b/4a
COLOURS	White and pastel tints from the Peintures Maestria
CONTAINER SIZE	5L - 15L

SURFACE PREPARATION | APPLICATION

As stated by DTU 59.1, all surfaces must be clean, dry and free of dirt.

Old glossy painted surfaces must be previously sanded or washed with an appropriate cleaner and then rinsed with water.

Apply ARTIKA in case of old damp stains.

Old lime based coating should be removed by washout. These recommendations do not override a specific description of the substrate.

Application conditions	DTU 59.1
Application equipment	Brush : Dilution Ready to use Roller : Dilution Ready to use Airless spray-gun : Dilution 5 to 10 %.
Practical coverage	10 to 13 m ² /l per coat depending on surface texture.
Thinner / Clean-up solvent	Water
Drying time (20°C -65% RH)	Dust free : 2 h Dry : 8 h Recoat : 24 h for stain blocking

OLEOMAT

SYSTEM RECOMMENDATIONS

Substrate	plaster	plasterboard, cement, previously painted surfaces in good condition
Primer coat	Apply 1 coat of IKARPRIM	Apply 1 coat of AQUASTRIA PRIMER or IMPRESSION PLACO or PRIM O 2010
Top coat		Apply 1 or 2 coats of OLEOMAT

SAFETY MEASURES

Storage	Can be kept for 1 year in unopened original container. Protect from freezing and high temperatures.
Précaution d emploi	Shake or stir before use. Use in well-ventilated areas. Keep out of reach of children. For personal protection, refer to the Safety Data Sheet (SDS).
Transport	Not subject to ADR regulations (European Agreement concerning the International Carriage of Dangerous Goods by Road).
Gestion des déchets	Close the container tightly after use. Do not dispose of residues in the sewer or with household waste. Please take your empty container to an approved collection center. Contact local authorities for information on disposal and collection procedures.