


OLEOMAT

Waterborne lime-based ceiling paint



PRODUCT OVERVIEW

New and maintenance work
Only used in dry rooms
Ideal for HQE projects

BENEFITS

Excellent application
Great hiding power
Blocks nicotine stains in 2 coats
Certified EUROPEAN ECOLABEL (VOC < 1 g/l)
Good wet scrub resistance (Class 2 according to NF EN 13300)
Can be applied using a "wet-on-wet" procedure

AFNOR Classification NFT 36 005 Rating Family I Class 2b/4a

TECHNICAL SPECIFICATIONS

Finish	: flat
Density	: 1.50 +/- 0,05 Kg/l
Solids by	: Weight: 60 +/- 2% Volume: 40 +/- 2%
VOC (directive 2004/42/CE)	: EU limit value for this product . (cat. A/a): 30 g/l (2010). This product contains max 10 g/IVOC
Flash point	: Not applicable
Gloss level at to 85°	: < 1,5 %
Practical coverage	: 10 to 13 m ² /l per coat depending on surface texture.
Drying time (20°C -65% RH)	: Dry : 8 h Recoat : 24 h for stain blocking
Colours	: White and pastel tints from the Peintures Maestria
Storage	: Can be kept for 1 year in unopened original container. Protect from freezing and high temperatures.



OLEOMAT

Waterborne lime-based ceiling paint

SURFACE PREPARATION

As stated by DTU 59.1, all surfaces must be clean, dry and free of dirt.

Old glossy painted surfaces must be previously sanded or washed with an appropriate cleaner and then rinsed with water.

Apply ARTIKA in case of old damp stains.

Old lime based coating should be removed by washout.

These recommendations do not override a specific description of the substrate.

APPLICATION

- Application conditions** : DTU 59.1
Application equipment : Brush, Roller, Airless spray-gun.
Clean-up solvent : Water
Thinner : Water
Dilution : Brush (Ready to use), Roller (Ready to use), Airless spray-gun (5 to 10 %).

SYSTEM RECOMMENDATIONS

Substrate	Primer coat	Top coat
plaster	Apply 1 coat of IKARPRIM	Apply 1 or 2 coats of OLEOMAT
plasterboard, cement, previously painted surfaces in good condition	Apply 1 coat of AQUASTRIA PRIMER or IMPRESSION PLACO or PRIM O 2010	

CONTAINER SIZE

5L - 15L

SAFETY MEASURES

Refer to the Safety Data Sheet