



# OLOXANE MAT

Waterborne interior siloxane-modified acrylic paint - Flat



## PRODUCT OVERVIEW

New and maintenance work  
Excellent top coat for interior walls and ceilings in dry rooms

## BENEFITS

Low odor  
High hiding power  
No yellowing (even in the dark)  
Fast drying and recoating  
Good wet scrub resistance (Class 2 according to NF EN 13300)

AFNOR Classification NFT 36 005 Rating Family I Class 7b2/10c

## TECHNICAL SPECIFICATIONS

<b>Finish</b>	: flat
<b>Density</b>	: 1.48 +/- 0,05 Kg/l
<b>Solids by</b>	: Weight: 57 +/- 2%      Volume: 37 +/- 2%
<b>VOC (directive 2004/42/CE)</b>	: EU limit value for this product . (cat. A/a): 30 g/l (2010). This product contains max 10 g/IVOC
<b>Flash point</b>	: Not applicable
<b>Gloss level at to 85°</b>	: < 3 %
<b>Practical coverage</b>	: 9 to 10 m <sup>2</sup> /l per coat depending on surface texture.
<b>Drying time (20°C -65% RH)</b>	: Dry                   : 2 h Recoat               : 6 h
<b>Colours</b>	: White and pastel tints from the Peintures Maestria
<b>Storage</b>	: Can be kept for 1 year in unopened original container. Protect from freezing and high temperatures.



## OLOXANE MAT

Waterborne interior siloxane-modified acrylic paint - Flat

### SURFACE PREPARATION

As stated by DTU 59.1, all surfaces must be clean, dry and free of dirt.

Old glossy painted surfaces must be previously sanded or washed with an appropriate cleaner and then rinsed with water.

Unpainted surfaces must be previously primed.

Old lime based coating should be removed by washout.

These recommendations do not override a specific description of the substrate.

### APPLICATION

- Application conditions** : DTU 59.1  
**Application equipment** : Brush, Roller, Airless spray-gun.  
**Clean-up solvent** : Water  
**Thinner** : Water  
**Dilution** : Brush (Ready to use), Roller (Ready to use), Airless spray-gun (5 to 10 %).

### SYSTEM RECOMMENDATIONS

Substrate	Primer coat	Top coat
plaster, old solventborne alkyd paint in good condition	Apply 1 coat of IKARPRIM	Apply 2 coats of OLOXANE MAT
plasterboard, cement coating, hydraulic binder-based coating	Apply 1 coat of PRIM O 2010	
previously painted surfaces in good condition		

### CONTAINER SIZE

15L

### SAFETY MEASURES

Refer to the Safety Data Sheet