



VERNIKAR

Solventborne interior & exterior wood varnish



PRODUCT OVERVIEW

Interior: VERNIKAR MAT (flat) Interior & exterior: VERNIKAR SATIN, VERNIKAR BRILLANT (high gloss) and VERNIKAR MARIN

BENEFITS

VERNIKAR MAT:

- Flat alkyd-urethane varnish
- Excellent levelling

VERNIKAR SATIN:

- Satin alkyd-urethane varnish
- Excellent levelling

VERNIKAR BRILLANT:

- Gloss alkyd-urethane varnish
- High gloss and excellent levelling

VERNIKAR MARIN:

- Very high-gloss marine varnish
- Excellent durability in marine atmosphere

TECHNICAL SPECIFICATIONS		
VOC	EU limit value for this product . (cat. A/e): 400 g/l (2010). This product contains max 400 g/IVOC	
FLASH POINT	23°C to 55°C	
AFNOR CLASSIFICATION NFT 36 005	Rating Family I Class 4a	
COLOURS	Colourless	
CONTAINER	1L - 5L	

1L - 5L

SURFACE PREPARATION | APPLICATION

SIZE

As stated by DTU 59.1, all surfaces must be clean, dry and free of dirt. For maintenance work, remove peeling paint by brushing, scraping or sanding. Old glossy painted surfaces must be sanded or washed with an appropriate cleaner and then rinsed with water.

If necessary, substrates must first be treated with a fungal treatment. These recommendations do not override a specific description of the substrate.

Application conditions	DTU 59.1
Application equipment	Brush : Dilution Ready to use.
Practical coverage	10 to 15 m²/l per coat depending on surface texture.
Thinner / Clean-up solvent	White spirit
Drying time (20°C -65% RH)	Dust free : / Dry : 4 to 5 h Recoat : 24 h





VERNIKAR

SYSTEM RECOMMENDATIONS		
Substrate	wood	
Primer coat	Apply 1 coat of VERNIKAR diluted to 5%	
Top coat	Apply 2 coats of VERNIKAR	

SAFETY MEASURES		
Storage	Can be kept for 1 year in unopened original container. Protect from freezing and high temperatures.	
Précaution d emploi	Shake or stir before use. Use in well-ventilated areas. Keep out of reach of children. For personal protection, refer to the Safety Data Sheet (SDS).	
Transport	Not subject to ADR regulations (European Agreement concerning the International Carriage of Dangerous Goods by Road).	
Gestion des déchets	Close the container tightly after use. Do not dispose of residues in the sewer or with household waste. Please take your empty container to an approved collection center. Contact local authorities for information on disposal and collection procedures.	

ISO 9001
ISO 14001
BUREAU VERITAS
Certification