



ARTIKA 2010

Solventborne lime modified oil primer



PRODUCT OVERVIEW

New and renovation work Ideal for stained ceilings Specially recommended for lime based coating

BENEFITS

Can be applied using a "wet-on-wet" procedure
Does not cause tension
Compatible with most surfaces
Excellent stain-blocking properties
High hiding power
Very low yellowing

TECHNICAL SPECIFICATIONS

FINISH	flat
DENSITY	1.47 +/- 0,05 Kg/l
SOLIDS BY	Weight : 70 +/- 2% Volume : 46 +/- 2%
VOC	EU limit value for this product (cat. A/g): 450 g/l (2007).. (cat. A/g): 350 g/l (2010). This product contains max 350 g/IVOC
FLASH POINT	above 60°C
GLOSS LEVEL AT	2.5% 85°
AFNOR CLASSIFICATION NFT 36 005	Rating Family I Class 2b
COLOURS	WHITE
CONTAINER SIZE	2.5L - 15L

SURFACE PREPARATION | APPLICATION

As stated by DTU 59.1, all surfaces must be clean, dry and free of dirt.
For maintenance work, remove peeling paint by brushing, scraping or sanding. Old glossy painted surfaces must be sanded or washed with an appropriate cleaner and then rinsed with water.
In the presence of contaminants such as mildew, molds or bacteria, apply an anti-fungal treatment named IKAR AM. These recommendations do not override a specific description of the substrate.

Application conditions	DTU 59.1
Application equipment	Brush : Dilution Ready to use Roller : Dilution Ready to use Airless spray-gun : Dilution Ready to use.
Practical coverage	11 to 15 m ² /l per coat depending on surface texture.
Thinner / Clean-up solvent	White spirit
Drying time (20°C -65% RH)	Dust free : 2 h Dry : 8 to 10 h Recoat : 24 h for stain blocking



ARTIKA 2010

SYSTEM RECOMMENDATIONS

Substrate	concrete, hydraulic binder based coating, cement	plaster
Primer coat	-	Apply 1 coat of ARTIKA 2010 or IKARPRIM
Top coat	Apply 2 coats of ARTIKA 2010	

SAFETY MEASURES

Storage	Can be kept for 1 year in unopened original container. Protect from freezing and high temperatures.
Précaution d emploi	Shake or stir before use. Use in well-ventilated areas. Keep out of reach of children. For personal protection, refer to the Safety Data Sheet (SDS).
Transport	Not subject to ADR regulations (European Agreement concerning the International Carriage of Dangerous Goods by Road).
Gestion des déchets	Close the container tightly after use. Do not dispose of residues in the sewer or with household waste. Please take your empty container to an approved collection center. Contact local authorities for information on disposal and collection procedures.