

BANDAX STADIUM

Marking paint for sport fields



Classement AFNOR NFT 36 005 Famille I Classe 7a2

DESCRIPTION

White, one-component, paint for drawing lines on sports fields, to be used exclusively on lawns and grass surfaces. Can be used with any application device. Can be used directly or diluted prior to use. Enables to reduce the coating schedule.

DESTINATION

Lawn marking for football, rugby and hockey pitches, golf courses, and tennis courts.

FONCTIONAL LIFESPAN

Dose	: 3-8 L for a rugby or football pitch.
Drying	: 45 minutes at 20°C

PROPERTIES

The paint provides long-lasting marking that remains visible even after rainfalls. Excellent whiteness during the day and at night, providing perfect visibility for marking purposes.

TECHNICAL FEATURES

Density	: 1.55 +/- 0.55 g/m ²
Storage	: 12 months in its unaltered and sealed original container, kept away from frost.
Colours	: White
Screnning	: 250 µm
Paint thinner	: Water
Clean-up solvent	: Water

BANDAX STADIUM

Marking paint for sport fields

APPLICATION

SURFACE PREPARATION

LAWN

Slightly dry or dam (application of dry grass slows down the drying).

CONDITION OF APPLICATION

Surface temperature: Between 5°C and 40°C and at least 3°C higher than the dew point in order to eliminate any risk of condensation. Atmospheric conditions: The temperature must be between 10°C and 40°C. The humidity must be between 0% and 85%.

EQUIPMENT AND DILUTION FOR APPLICATION

Pneumatic

- Nozzle : depends on the equipment used. - Pressure in vat. : depends on the equipment used.

Airless

- Nozzle : depends on the equipment used. - Pressure in vat. : depends on the equipment used.

PRODUCT PREPARATION

BANDAX STADIUM

The BANDAX STADIUM paint is ready for use but can also be diluted in 10% water for the coating over of existing white lines.

CLEANING

Water cleaning for equipment and nozzles.

PACKAGING

White : 15L.