

BIONYL SATIN

Waterborne interior acrylic paint - Satin



PRODUCT OVERVIEW

Specially designed for large surfaces areas such as commercial sites, parking lots' walls

BENEFITS

- Odourless
- Good water vapour permeability
- High hiding power
- Great adhesion
- Quick drying
- No yellowing
- Wet scrub resistance (Class 2 according to NF EN 13300)

TECHNICAL SPECIFICATIONS

CERTIFICATIONS	
FINISH	satin
DENSITY	1.29 +/- 0,05 Kg/l
SOLIDS BY	Weight : 53 +/- 2% Volume : 40 +/- 2%
VOC	EU limit value for this product . (cat. A/a): 30 g/l (2010). This product contains max 15 g/IVOC
FLASH POINT	Not applicable
GLOSS LEVEL AT	10 ± 2 % 60°
AFNOR CLASSIFICATION NFT 36 005	Rating Family I Class 7b2
COLOURS	White
CONTAINER SIZE	15L

SURFACE PREPARATION | APPLICATION

As stated by DTU 59.1, all surfaces must be clean, dry and free of dirt.
Old glossy painted surfaces must be previously sanded or washed with an appropriate cleaner and then rinsed with water.
Do not apply without proper ventilation. These recommendations do not override a specific description of the substrate.

Application conditions	DTU 59.1
Application equipment	Brush : Dilution Ready to use Roller : Dilution Ready to use Airless spray-gun : Dilution Ready to use.
Practical coverage	11 to 13 m²/l per coat depending on surface texture.
Thinner / Clean-up solvent	Water
Drying time (20°C -65% RH)	Dust free : / Dry : 1 to 2 h Recoat : 6 h



BIONYL SATIN

SYSTEM RECOMMENDATIONS

Substrate	concrete, hydraulic binder-based coating, plasterboard	plaster	previously painted surfaces in good condition
Primer coat	Apply 1 coat of PRIM O 2010 or IMPRESSION PLACO	Apply 1 coat of IKARPRIM	-
Top coat	Apply 2 coats of BIONYL SATIN		

SAFETY MEASURES

Storage	Can be kept for 1 year in unopened original container. Protect from freezing and high temperatures.
Précaution d emploi	Shake or stir before use. Use in well-ventilated areas. Keep out of reach of children. For personal protection, refer to the Safety Data Sheet (SDS).
Transport	Not subject to ADR regulations (European Agreement concerning the International Carriage of Dangerous Goods by Road).
Gestion des déchets	Close the container tightly after use. Do not dispose of residues in the sewer or with household waste. Please take your empty container to an approved collection center. Contact local authorities for information on disposal and collection procedures.