

DECONATURE IMPRESSION

Waterborne interior acrylic-alkyd primer





PRODUCT OVERVIEW

Primer for a wide variety of surface such as hydraulic binder-based coating, plasterboard, cement rendering, wood and wood joinery

BENEFITS

Good sealing properties
Excellent adhesion
Odourless
Certified European Ecolabel (VOC 1 g/l)

TECHNICAL SPECIFICATIONS

CERTIFICATIONS	  EU ECOLABEL : FR/044/014
FINISH	flat
DENSITY	1.40 +/- 0,05 Kg/l
SOLIDS BY	Weight : 58 +/- 2% Volume : 40 +/- 2%
VOC	EU limit value for this product (cat. A/g): 50 g/l (2007),. (cat. A/g): 30 g/l (2010). This product contains max 1 g/IVOC
FLASH POINT	Not applicable
GLOSS LEVEL AT	5 % 85°
AFNOR CLASSIFICATION NFT 36 005	Rating Family I Class 4a/7b2
COLOURS	White
CONTAINER SIZE	2.5L - 15L

SURFACE PREPARATION | APPLICATION

As stated by DTU 59.1, all surfaces must be clean, dry and free of dirt.
For maintenance work, remove peeling paint by brushing, scraping or sanding. Old glossy painted surfaces must be sanded or washed with an appropriate cleaner and then rinsed with water.
In the presence of contaminants such as mildew, molds or bacteria, apply an anti-fungal treatment named IKAR BACTERICIDE. These recommendations do not override a specific description of the substrate.

Application conditions	DTU 59.1
Application equipment	Brush : Dilution 0 to 3 % Roller : Dilution 0 to 3 %.
Practical coverage	7 to 9 m ² /l per coat depending on surface texture.
Thinner / Clean-up solvent	Water
Drying time (20°C -65% RH)	Dry : 1 to 2 h Recoat : 6 h

DECONATURE IMPRESSION

SYSTEM RECOMMENDATIONS

Substrate	wood and wood joinery, hydraulic binder-based coating, cement rendering, plasterboard
Primer coat	Apply 1 coat of DECONATURE IMPRESSION
Top coat	Apply 1 or 2 coats of DECONATURE MAT, DECONATURE VELOURS or DECONATURE SATIN

SAFETY MEASURES

Storage	Can be kept for 1 year in unopened original container. Protect from freezing and high temperatures.
Précaution d emploi	Shake or stir before use. Use in well-ventilated areas. Keep out of reach of children. For personal protection, refer to the Safety Data Sheet (SDS).
Transport	Not subject to ADR regulations (European Agreement concerning the International Carriage of Dangerous Goods by Road).
Gestion des déchets	Close the container tightly after use. Do not dispose of residues in the sewer or with household waste. Please take your empty container to an approved collection center. Contact local authorities for information on disposal and collection procedures.