

EXCELIOR BRILLANT

Waterborne alkyd urethane paint - High gloss



PRODUCT OVERVIEW

New and maintenance work Residential and commercial sites
Excellent top coat for interior walls in dry and wet rooms Top coat for interior and exterior wood and wood joinery

BENEFITS

High scratch and impact resistance
Excellent wet scrub resistance (Class 1 according to NF EN 13300)
Good hiding power
Low odour
Quick drying

TECHNICAL SPECIFICATIONS

DENSITY	1.30 +/- 0,05 Kg/l
SOLIDS BY	Weight : 54 +/- 2% Volume : 40 +/- 2%
VOC	EU limit value for this product (cat. A/a): 75 g/l (2007).. (cat. A/a): 30 g/l (2010). This product contains max 30 g/IVOC
FLASH POINT	Not applicable
GLOSS LEVEL AT	75 +/- 5 % 60°
AFNOR CLASSIFICATION NFT 36 005	Rating Family I Class 4a/6a -7b2
COLOURS	White, medium and deep tints from the Peintures Maestria colour chart
CONTAINER SIZE	0.5L - 2.5L - 10L

SURFACE PREPARATION | APPLICATION

As stated by DTU 59.1, all surfaces must be clean, dry and free of dirt.
Old glossy painted surfaces must be previously sanded or washed with an appropriate cleaner and then rinsed with water.
Metals must be primed with a suitable primer.
Tannin containing wood should be primed with a tannin blocking primer.
In the presence of contaminants such as mildew, molds or bacteria, apply an anti-fungal treatment named IKAR AM. These recommendations do not override a specific description of the substrate.

Application conditions	DTU 59.1
Application equipment	Brush : Dilution Ready to use Roller : Dilution Ready to use Enamel roller : Dilution Ready to use. Airless spray-gun : Dilution 5 to 10 %.
Practical coverage	10 to 14 m²/l per coat depending on surface texture.
Thinner / Clean-up solvent	Water
Drying time (20°C -65% RH)	Dry : 1 to 2 h Recoat : 24 h



EXCELIOR BRILLANT

SYSTEM RECOMMENDATIONS

Substrate	hydraulic binder-based coating, plasterboard, previously painted surfaces in good condition, interior and exterior wood and wood joinery	plaster	ferrous metals
Primer coat	Apply 1 coat of PRIM O 2010	Apply 1 coat of IKARPRIM	Apply 1 coat of ZINCOLAC O
Top coat	Apply 2 coats of EXCELIOR BRILLANT		

SAFETY MEASURES

Storage	Can be kept for 1 year in unopened original container. Protect from freezing and high temperatures.
Précaution d emploi	Shake or stir before use. Use in well-ventilated areas. Keep out of reach of children. For personal protection, refer to the Safety Data Sheet (SDS).
Transport	Not subject to ADR regulations (European Agreement concerning the International Carriage of Dangerous Goods by Road).
Gestion des déchets	Close the container tightly after use. Do not dispose of residues in the sewer or with household waste. Please take your empty container to an approved collection center. Contact local authorities for information on disposal and collection procedures.