



IKARBOIS

Solventborne interior & exterior wood stain




PRODUCT OVERVIEW

New and maintenance work Impregnation wood stain (colourless or pigmented) Excellent decoration and protection for wood and wood joinery

BENEFITS

Great water repellency
Excellent UV and weather resistance
Microporous

TECHNICAL SPECIFICATIONS

CERTIFICATIONS	
FINISH	satin
DENSITY	0.84 +/- 0,05 Kg/l
SOLIDS BY	Weight : 27 +/- 2% Volume : 22 +/- 2%
VOC	EU limit value for this product . (cat. A/f): 700 g/l (2010). This product contains max 650 g/IVOC
FLASH POINT	23°C to 55°C
AFNOR CLASSIFICATION NFT 36 005	Rating Family I Class 4a
COLOURS	IKARBOIS colour chart
CONTAINER SIZE	1L - 5L

SURFACE PREPARATION | APPLICATION

As stated by DTU 59.1, all surfaces must be clean, dry and free of dirt. For maintenance work, remove peeling paint by brushing, scraping or sanding. Old glossy painted surfaces must be sanded or washed with an appropriate cleaner and then rinsed with water.

If necessary, substrates must first be treated with a fungal treatment.

NOTE: Tints give variable results depending on wood specie. A preliminary adherence test must be carried out.

These recommendations do not override a specific description of the substrate.

Application conditions	DTU 59.1
Application equipment	Brush : Dilution Ready to use Airless spray-gun : Dilution Ready to use. Dipping : Dilution Ready to use.
Practical coverage	8 to 16 m ² /l per coat depending on surface texture.
Thinner / Clean-up solvent	White spirit
Drying time (20°C -65% RH)	Dust free : 3 to 6 h Dry : 24 to 48 h Recoat : 24 to 48 h depending on wood specie



IKARBOIS

SYSTEM RECOMMENDATIONS

Substrate	wood and wood joinery, stripped wood	anti-drying wood such as Iroko
Primer coat	Apply 1 coat of IKARBOIS	Apply 1 coat of suitable primer
Top coat	exterior: Apply 2 coats of IKARBOIS SATIN THIXO interior: Apply 1 coat of IKARBOIS SATIN THIXO	

SAFETY MEASURES

Storage	Can be kept for 1 year in unopened original container. Protect from freezing and high temperatures.
Précaution d emploi	Shake or stir before use. Use in well-ventilated areas. Keep out of reach of children. For personal protection, refer to the Safety Data Sheet (SDS).
Transport	Not subject to ADR regulations (European Agreement concerning the International Carriage of Dangerous Goods by Road).
Gestion des déchets	Close the container tightly after use. Do not dispose of residues in the sewer or with household waste. Please take your empty container to an approved collection center. Contact local authorities for information on disposal and collection procedures.