

IKARFIX IP

Waterborne interior & exterior acrylic primer



PRODUCT OVERVIEW

Residential and commercial sites Specially recommended after chemical pickling

BENEFITS

Excellent adhesion (despite the presence of paraffin residuals)
Great hiding power
Microporous

TECHNICAL SPECIFICATIONS

FINISH	flat
DENSITY	1.44 +/- 0,05 Kg/l
SOLIDS BY	Weight : 64 +/- 2% Volume : 48 +/- 2%
VOC	EU limit value for this product . (cat. A/h): 30 g/l (2010). This product contains max 30 g/IVOC
FLASH POINT	Not applicable
GLOSS LEVEL AT	10% 60°
AFNOR CLASSIFICATION NFT 36 005	Rating Family I Class 7b2
COLOURS	White
CONTAINER SIZE	20 KG

SURFACE PREPARATION | APPLICATION

As stated by DTU 59.1, all surfaces must be clean, dry and free of dirt.

Interior: Old glossy painted surfaces must be previously sanded or washed with an appropriate cleaner and then rinsed with water.

In the presence of contaminants such as mildew, molds or bacteria, apply an anti-fungal treatment named IKAR BACTERICIDE.

Exterior: if required a high-pressure cleaning must be carried out, followed by the application of an anti-fungal treatment named IKAR BACTERICIDE.
These recommendations do not override a specific description of the substrate.

Application conditions	DTU 59.1
Application equipment	Brush : Dilution 0 to 5 % Facade roller : Dilution 0 to 5 %.
Practical coverage	150 to 200 gr/m ² per coat depending on surface texture.
Thinner / Clean-up solvent	Water
Drying time (20°C -65% RH)	Dust free : 20 mn Dry : 1 h Recoat : 12 h

IKARFIX IP

SYSTEM RECOMMENDATIONS

Substrate	concrete, cement, hydraulic binder-based coating, previously painted surfaces in good condition
Primer coat	Apply 1 coat of IKARFIX IP
Top coat	Apply 1 or 2 coats of interior or exterior paints

SAFETY MEASURES

Storage	Can be kept for 1 year in unopened original container. Protect from freezing and high temperatures.
Précaution d emploi	Shake or stir before use. Use in well-ventilated areas. Keep out of reach of children. For personal protection, refer to the Safety Data Sheet (SDS).
Transport	Not subject to ADR regulations (European Agreement concerning the International Carriage of Dangerous Goods by Road).
Gestion des déchets	Close the container tightly after use. Do not dispose of residues in the sewer or with household waste. Please take your empty container to an approved collection center. Contact local authorities for information on disposal and collection procedures.