

IKARFIX O

Waterborne interior & exterior acrylic paint



PRODUCT OVERVIEW

New and maintenance work Commercial and residential sites in dry and wet rooms

BENEFITS

Excellent adhesion
Good alkali resistance
Great hiding power
Microporous

TECHNICAL SPECIFICATIONS

| | |
|------------------------------------|------------------------------------------------------------------------------------------------------------|
| DENSITY | 1.54 +/- 0,05 Kg/l |
| SOLIDS BY | Weight : 68 +/- 2% Volume : 50 +/- 2% |
| VOC | EU limit value for this product . (cat. A/h): 30 g/l (2010). This product contains max 30 g/IVOC |
| FLASH POINT | Not applicable |
| AFNOR CLASSIFICATION NFT 36 005 | Rating Family I Class 7b2 |
| COLOURS | White |
| CONTAINER SIZE | 7KG / 20KG |

SURFACE PREPARATION | APPLICATION

As stated by DTU 59.1, all surfaces must be clean, dry and free of dirt.

Interior: Old glossy painted surfaces must be previously sanded or washed with an appropriate cleaner and then rinsed with water.

In the presence of contaminants such as mildew, molds or bacteria, apply an anti-fungal treatment named IKAR AM.

Exterior: if required a high-pressure cleaning must be carried out, followed by the application of an anti-fungal treatment named IKAR AM.

For powdery surface, apply 1 coat of IKARFIX S. These recommendations do not override a specific description of the substrate.

| | |
|-----------------------------------|-------------------------------------------------------------------------|
| Application conditions | DTU 59.1 |
| Application equipment | Brush : Dilution Ready to use Facade roller : Dilution Ready to use. |
| Practical coverage | 150 to 200 gr/m ² per coat depending on surface texture. |
| Thinner / Clean-up solvent | Water |
| Drying time (20°C -65% RH) | Dust free : 20 mn Dry : 1 h Recoat : 12 h |



IKARFIX O

SYSTEM RECOMMENDATIONS

| | |
|--------------------|---------------------------------------------------------|
| Substrate | concrete, cement, hydraulic binder-based coating |
| Primer coat | Apply 1 coat of IKARFIX O |
| Top coat | Apply 1 or 2 coats of interior or exterior paints |

SAFETY MEASURES

| | |
|----------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Storage | Can be kept for 1 year in unopened original container. Protect from freezing and high temperatures. |
| Précaution d emploi | Shake or stir before use. Use in well-ventilated areas. Keep out of reach of children. For personal protection, refer to the Safety Data Sheet (SDS). |
| Transport | Not subject to ADR regulations (European Agreement concerning the International Carriage of Dangerous Goods by Road). |
| Gestion des déchets | Close the container tightly after use. Do not dispose of residues in the sewer or with household waste. Please take your empty container to an approved collection center. Contact local authorities for information on disposal and collection procedures. |