



IKARSOIE

Solventborne interior alkyd urethane paint - Satin



PRODUCT OVERVIEW

New and maintenance work Ideal for use on interior wood and wood joinery

BENEFITS

High hiding power
Fast drying
Washable

TECHNICAL SPECIFICATIONS

FINISH	satin
DENSITY	1.29 +/- 0,05 Kg/l
SOLIDS BY	Weight : 70 +/- 2% Volume : 53 +/- 2%
VOC	EU limit value for this product (cat. A/d): 400 g/l (2007), (cat. A/d): 300 g/l (2010). This product contains max 300 g/l VOC
FLASH POINT	23°C to 55°C
GLOSS LEVEL AT	20 ± 5% 60°
AFNOR CLASSIFICATION NFT 36 005	Rating Family I Class 4a
COLOURS	White, medium and deep tints from the Peintures Maestria colour chart
CONTAINER SIZE	0.5L - 2.5L - 10L

SURFACE PREPARATION | APPLICATION

As stated by DTU 59.1, all surfaces must be clean, dry and free of dirt.

For maintenance work, remove peeling paint by brushing, scraping or sanding. Old glossy painted surfaces must be sanded or washed with an appropriate cleaner and then rinsed with water. These recommendations do not override a specific description of the substrate.

Application conditions	DTU 59.1
Application equipment	Brush : Dilution Ready to use Roller : Dilution Ready to use Airless spray-gun : Dilution Ready to use.
Practical coverage	10 to 12 m ² /l per coat depending on surface texture.
Thinner / Clean-up solvent	White spirit
Drying time (20°C -65% RH)	Dust free : 3 h Dry : 8 to 10 h Recoat : 24 h

IKARSOIE

SYSTEM RECOMMENDATIONS

Substrate	wood and wood joinery	previously painted surfaces in good condition
Primer coat	Apply 1 coat of IKARPRIM	-
Top coat		Apply 2 coats of IKARSOIE

SAFETY MEASURES

Storage	Can be kept for 1 year in unopened original container. Protect from freezing and high temperatures.
Précaution d emploi	Shake or stir before use. Use in well-ventilated areas. Keep out of reach of children. For personal protection, refer to the Safety Data Sheet (SDS).
Transport	Not subject to ADR regulations (European Agreement concerning the International Carriage of Dangerous Goods by Road).
Gestion des déchets	Close the container tightly after use. Do not dispose of residues in the sewer or with household waste. Please take your empty container to an approved collection center. Contact local authorities for information on disposal and collection procedures.