



IKARWOOD SATIN

Solventborne interior & exterior alkyd paint - Satin



PRODUCT OVERVIEW

New and maintenance work Can be used as primer and top coat
Ideal for use on properly prepared wood and wood joinery
Specially recommended for exterior use

BENEFITS

Microporous
Great hardness
High block resistance

TECHNICAL SPECIFICATIONS

FINISH	satin
DENSITY	1.37 +/- 0,05 Kg/l
SOLIDS BY	Weight : 73 +/- 2% Volume : 55 +/- 2%
VOC	EU limit value for this product . (cat. A/d): 300 g/l (2010). This product contains max 300 g/IVOC
FLASH POINT	23°C to 55°C
GLOSS LEVEL AT	35 60°
AFNOR CLASSIFICATION NFT 36 005	Rating Family I Class 4a
COLOURS	White, medium and depp tints from the Peintures Maestria colour chart
CONTAINER SIZE	0.5L - 2.5L - 10L

SURFACE PREPARATION | APPLICATION

As stated by DTU 59.1, all surfaces must be clean, dry and free of dirt.
For maintenance work, remove peeling paint by brushing, scraping or sanding. Old glossy painted surfaces must be sanded or washed with an appropriate cleaner and then rinsed with water.
If necessary, substrates must first be treated with a fungal treatment.

These recommendations do not override a specific description of the substrate.

Application conditions	DTU 59.1
Application equipment	Brush : Dilution Ready to use Roller : Dilution Ready to use Airless spray-gun : Dilution Ready to use.
Practical coverage	9 to 13 m ² /l per coat depending on surface texture.
Thinner / Clean-up solvent	White spirit
Drying time (20°C -65% RH)	Dust free : 3 h Dry : 8 to 10 h Recoat : 24 h



IKARWOOD SATIN

SYSTEM RECOMMENDATIONS

Substrate	wood and wood joinery, previously painted surfaces in good condition	new or stripped wood
Primer coat	-	Apply 1 coat of IKARWOOD SATIN diluted with 10 % of White Spirit
Top coat	Interior : Apply 1 or 2 coats of IKARWOOD SATIN Exterior : Apply 2 coats of IKARWOOD SATIN	

SAFETY MEASURES

Storage	Can be kept for 1 year in unopened original container. Protect from freezing and high temperatures.
Précaution d emploi	Shake or stir before use. Use in well-ventilated areas. Keep out of reach of children. For personal protection, refer to the Safety Data Sheet (SDS).
Transport	Not subject to ADR regulations (European Agreement concerning the International Carriage of Dangerous Goods by Road).
Gestion des déchets	Close the container tightly after use. Do not dispose of residues in the sewer or with household waste. Please take your empty container to an approved collection center. Contact local authorities for information on disposal and collection procedures.