

# IMPRESSION PLACO

Waterborne interior acrylic primer



EU ECOLABEL : FR/044/014

## PRODUCT OVERVIEW

New and maintenance work  
Primer for low porosity surfaces in good condition  
Ideal for HQE projects

## BENEFITS

Odourless  
High hiding power  
Good adhesion  
Great sealing properties  
Certified EUROPEAN ECOLABEL

AFNOR Classification NFT 36 005 Rating Family I Class 7b2

## TECHNICAL SPECIFICATIONS

<b>Finish</b>	: flat
<b>Density</b>	: 1.67 +/- 0,05 Kg/l
<b>Solids by</b>	: Weight: 68 +/- 2%      Volume: 47 +/- 2%
<b>VOC (directive 2004/42/CE)</b>	: EU limit value for this product . (cat. A/g): 30 g/l (2010). This product contains max 10 g/IVOC
<b>Flash point</b>	: Not applicable
<b>Gloss level at 60°</b>	: < 10 %
<b>Practical coverage</b>	: 5 to 10 m²/l per coat depending on surface texture.
<b>Drying time (20°C -65% RH)</b>	: Dry : 1 h Recoat : 2 h
<b>Colours</b>	: White
<b>Storage</b>	: Can be kept for 1 year in unopened original container. Protect from freezing and high temperatures.

## IMPRESSION PLACO

Waterborne interior acrylic primer



### SURFACE PREPARATION

As stated by DTU 59.1, all surfaces must be clean, dry and free of dirt.

For maintenance work, remove peeling paint by brushing, scraping or sanding. Old glossy painted surfaces must be sanded or washed with an appropriate cleaner and then rinsed with water.

In the presence of contaminants such as mildew, molds or bacteria, apply an anti-fungal treatment named IKAR BACTERICIDE.

These recommendations do not override a specific description of the substrate.

### APPLICATION

<b>Application conditions</b>	: DTU 59.1
<b>Application equipment</b>	: Brush, Roller, Airless spray-gun.
<b>Clean-up solvent</b>	: Water
<b>Thinner</b>	: Water
<b>Dilution</b>	: Brush (5 to 10 %), Roller (5 to 10 %), Airless spray-gun (5 to 10 %).

### SYSTEM RECOMMENDATIONS

Substrate	Primer coat	Top coat
plasterboard, concrete, hydraulic binder-based coating, unstained surfaces in good condition	Apply 1 coat of IMPRESSION PLACO	Apply 1 or 2 coats of waterborne alkyd or acrylic paint
stained surfaces	Apply 1 coat of NORWAY or IKARPRIM	
plaster	Apply 1 coat of IKARPRIM	

### CONTAINER SIZE

15L

### SAFETY MEASURES

Refer to the Safety Data Sheet