



# LATEXOR

Waterborne interior & exterior acrylic paint



## PRODUCT OVERVIEW

New and maintenance work Residential and commercial sites

## BENEFITS

Excellent alkali resistance  
 Good adhesion  
 High hiding power  
 Excellent UV resistance  
 Wide range of colours  
 Good leveling  
 Washable  
 Good wet scrub resistance (Class 2 according to NF EN 13300)  
 French classification D2 - Standard P84.403  
 European classification G3E3S1V2W1A0C0 - Standard EN 1062-1

## TECHNICAL SPECIFICATIONS

FINISH	flat
DENSITY	1.53 +/- 0,05 Kg/l
SOLIDS BY	Weight : 67 +/- 2% Volume : 50 +/- 2%
VOC	EU limit value for this product (cat. A/c): 75 g/l (2007).. (cat. A/c): 30 g/l (2010). <b>This product contains max 1 g/IVOC</b>
FLASH POINT	Not applicable
GLOSS LEVEL AT	5 % 85°
AFNOR CLASSIFICATION NFT 36 005	Rating Family I Class 7b2
COLOURS	White, medium and deep tints from the Peintures Maestria colour chart
CONTAINER SIZE	0.5L - 2.5L - 15L

## SURFACE PREPARATION | APPLICATION

As stated by DTU 59.1, all surfaces must be clean, dry and free of dirt.

Interior: Old glossy painted surfaces must be previously sanded or washed with an appropriate cleaner and then rinsed with water.

In the presence of contaminants such as mildew, molds or bacteria, apply an anti-fungal treatment named IKAR AM.

Exterior: if required an high-pressure cleaning must be carried out, followed by the application of an anti-fungal treatment named IKAR AM. These recommendations do not override a specific description of the substrate.

<b>Application conditions</b>	DTU 59.1
<b>Application equipment</b>	Brush : Dilution 0 to 3 % Roller : Dilution 0 to 3 % Facade roller : Dilution Ready to use Airless spray-gun : Dilution 3 to 5 %.
<b>Practical coverage</b>	6 to 9 m <sup>2</sup> /l per coat depending on surface texture.
<b>Thinner / Clean-up solvent</b>	Water
<b>Drying time (20°C -65% RH)</b>	Dust free : 20 mn Dry : 1 h Recoat : 4 h



## LATEXOR

### SYSTEM RECOMMENDATIONS

Substrate	Exterior: concrete, hydraulic binder-based coating	plaster	Interior: concrete, hydraulic binder-based coating, plasterboard
Primer coat	Apply 1 coat of IKARFIX S or IKARFIX O	Apply 1 coat of IKARPRIM	Apply 1 coat of PRIM O 2010 or AQUASTRIA PRIMER
Top coat	Apply 2 coats of LATEXOR		

### SAFETY MEASURES

<b>Storage</b>	Can be kept for 1 year in unopened original container. Protect from freezing and high temperatures.
<b>Précaution d emploi</b>	Shake or stir before use. Use in well-ventilated areas. Keep out of reach of children. For personal protection, refer to the Safety Data Sheet (SDS).
<b>Transport</b>	Not subject to ADR regulations (European Agreement concerning the International Carriage of Dangerous Goods by Road).
<b>Gestion des déchets</b>	Close the container tightly after use. Do not dispose of residues in the sewer or with household waste. Please take your empty container to an approved collection center. Contact local authorities for information on disposal and collection procedures.