



MULTIWAY

Waterborne interior & exterior acrylic paint - Velvet



PRODUCT OVERVIEW

New and maintenance work Multi-surface paint for interior and exterior Perfect adhesion to a wide range of substrates (VOC 5 g/l)

BENEFITS

Good alkali resistance
Excellent adhesion
Great UV resistance
High wet scrub resistance (Class 1 according to NF EN 13300)
Contains an anti-rust additive

TECHNICAL SPECIFICATIONS

CERTIFICATIONS	 
FINISH	silky satin
DENSITY	1.33 +/- 0,05 Kg/l
SOLIDS BY	Weight : 57 +/- 2% Volume : 43 +/- 2%
VOC	EU limit value for this product (cat. A/a): 75 g/l (2007), (cat. A/a): 30 g/l (2010). This product contains max 5 g/l VOC
FLASH POINT	Not applicable
GLOSS LEVEL AT	8-12 % 85°
AFNOR CLASSIFICATION NFT 36 005	Rating Family I Class 7b2
COMMENTAIRE	5 to 6 m ² /l for outdoors - 9 to 10 m ² /l for indoors
COLOURS	White, medium and deep tints from the Peintures Maestria colour chart
CONTAINER SIZE	2.5L - 15L

SURFACE PREPARATION | APPLICATION

As stated by DTU 59.1, all surfaces must be clean, dry and free of dirt.

Interior: Old glossy painted surfaces must be previously sanded or washed with an appropriate cleaner and then rinsed with water.

In the presence of contaminants such as mildew, molds or bacteria, apply an anti-fungal treatment named IKAR AM.

Exterior: if required an high-pressure cleaning must be carried out, followed by the application of an anti-fungal treatment named IKAR AM.

Unpainted metals should be sanded and the grease removed using a non-greasy solvent beforehand before priming. These recommendations do not override a specific description of the substrate.

Application conditions	DTU 59.1
Application equipment	Brush : Dilution Ready to use Roller : Dilution 0 to 5 % Facade roller : Dilution 0 to 5 % Airless spray-gun : Dilution 3 to 5 %.
Practical coverage	5 to 10 m ² /l per coat depending on surface texture.
Thinner / Clean-up solvent	Water
Drying time (20°C -65% RH)	Dust free : 20 mn Dry : 4 h Recoat : 6 h

MULTIWAY

SYSTEM RECOMMENDATIONS

Substrate	interior & exterior: concrete, hydraulic binder-based coating, cement, stripped galvanised metals, PVC, previously painted surfaces in good condition	interior: plasterboard, porous concrete, protected ferrous metals	interior: wood joinery with a risk of tannin staining
Primer coat	Apply 1 coat of MULTIWAY diluted to 5 %	Apply 1 coat of MULTIWAY diluted to 5 %	Apply 1 coat of NORWAY
Top coat	Apply 2 coats of MULTIWAY		

SAFETY MEASURES

Storage	Can be kept for 1 year in unopened original container. Protect from freezing and high temperatures.
Précaution d emploi	Shake or stir before use. Use in well-ventilated areas. Keep out of reach of children. For personal protection, refer to the Safety Data Sheet (SDS).
Transport	Not subject to ADR regulations (European Agreement concerning the International Carriage of Dangerous Goods by Road).
Gestion des déchets	Close the container tightly after use. Do not dispose of residues in the sewer or with household waste. Please take your empty container to an approved collection center. Contact local authorities for information on disposal and collection procedures.