

NORWAY

Waterborne interior stain blocking primer



PRODUCT OVERVIEW

New and renovation work
Ideal for a wide range of substrates

BENEFITS

High hiding power
Heavy stain blocking properties
Excellent adhesion
Microporous

AFNOR Classification NFT 36 005 Family I Class 10g

TECHNICAL SPECIFICATIONS

| | | |
|-----------------------------------|--|---------------------------|
| Density | : 1.46 +/- 0,05 Kg/l | |
| Solids by | : Weight: 58 +/- 2% | Volume: 39 +/- 2% |
| VOC (directive 2004/42/CE) | : EU limit value for this product (cat. A/g): 50 g/l (2007),. (cat. A/g): 30 g/l (2010). This product contains max 30 g/IVOC | |
| Flash point | : Not applicable | |
| Gloss level at 85° | : 15 +/- 5% | |
| Practical coverage | : 7 to 15 m²/l per coat depending on surface texture. | |
| Drying time (20°C -65% RH) | : Dry | : 2 h |
| | : Recoat | : 24 h for stain blocking |
| Colours | : White | |
| Storage | : Can be kept for 1 year in unopened original container. | |
| | Protect from freezing and high temperatures. | |



NORWAY

Waterborne interior stain blocking primer

SURFACE PREPARATION

As stated by DTU 59.1, all surfaces must be clean, dry and free of dirt.

For maintenance work, remove peeling paint by brushing, scraping or sanding. Old glossy painted surfaces must be sanded or washed with an appropriate cleaner and then rinsed with water.

In the presence of contaminants such as mildew, molds or bacteria, apply an anti-fungal treatment named IKAR BACTERICIDE.

Do not mix with other paints.

Do not apply on glass fabric, PVC or lime based coating.

These recommendations do not override a specific description of the substrate.

APPLICATION

| | |
|-------------------------------|--|
| Application conditions | : DTU 59.1 |
| Application equipment | : Brush, Roller. |
| Clean-up solvent | : Water |
| Thinner | : Water |
| Dilution | : Brush (Ready to use), Roller (Ready to use). |

SYSTEM RECOMMENDATIONS

| Substrate | Primer coat | Top coat |
|---|--|--|
| concrete, mineral coatings, plasterboard, stripped non-ferrous metals, stained surfaces | Apply 1 coat of Norway | Apply 1 or 2 coats of a suitable waterborne interior acrylic or alkyd paint |
| plaster | Apply 1 coat of IKARPRIM | |
| previously painted surfaces in good condition, wood and wood joinery | | |
| ferrous metals | Apply 1 coat of FERROSOTER PRIMAIRE | |

CONTAINER SIZE

2.5L - 15L

SAFETY MEASURES

Refer to the Safety Data Sheet