

OLOXANE MAT

Waterborne interior siloxane-modified acrylic paint - Flat



PRODUCT OVERVIEW

New and maintenance work Excellent top coat for interior walls and ceilings in dry rooms

BENEFITS

Low odor
High hiding power
No yellowing (even in the dark)
Fast drying and recoating
Good wet scrub resistance (Class 2 according to NF EN 13300)

TECHNICAL SPECIFICATIONS

FINISH	flat
DENSITY	1.48 +/- 0,05 Kg/l
SOLIDS BY	Weight : 57 +/- 2% Volume : 37 +/- 2%
VOC	EU limit value for this product . (cat. A/a): 30 g/l (2010). This product contains max 10 g/IVOC
FLASH POINT	Not applicable
GLOSS LEVEL AT	3 % 85°
AFNOR CLASSIFICATION NFT 36 005	Rating Family I Class 7b2/10c
COLOURS	White and pastel tints from the Peintures Maestria
CONTAINER SIZE	15L

SURFACE PREPARATION | APPLICATION

As stated by DTU 59.1, all surfaces must be clean, dry and free of dirt.
Old glossy painted surfaces must be previously sanded or washed with an appropriate cleaner and then rinsed with water.
Unpainted surfaces must be previously primed.
Old lime based coating should be removed by washout.
These recommendations do not override a specific description of the substrate.

Application conditions	DTU 59.1
Application equipment	Brush : Dilution Ready to use Roller : Dilution Ready to use Airless spray-gun : Dilution 5 to 10 %.
Practical coverage	9 to 10 m²/l per coat depending on surface texture.
Thinner / Clean-up solvent	Water
Drying time (20°C -65% RH)	Dry : 2 h Recoat : 6 h



OLOXANE MAT

SYSTEM RECOMMENDATIONS

Substrate	plaster, old solventborne alkyd paint in good condition	plasterboard, cement coating, hydraulic binder-based coating	previously painted surfaces in good condition
Primer coat	Apply 1 coat of IKARPRIM	Apply 1 coat of PRIM O 2010	-
Top coat	Apply 2 coats of OLOXANE MAT		

SAFETY MEASURES

Storage	Can be kept for 1 year in unopened original container. Protect from freezing and high temperatures.
Précaution d emploi	Shake or stir before use. Use in well-ventilated areas. Keep out of reach of children. For personal protection, refer to the Safety Data Sheet (SDS).
Transport	Not subject to ADR regulations (European Agreement concerning the International Carriage of Dangerous Goods by Road).
Gestion des déchets	Close the container tightly after use. Do not dispose of residues in the sewer or with household waste. Please take your empty container to an approved collection center. Contact local authorities for information on disposal and collection procedures.