

PRESTOLITE

Solventborne exterior PLIOLITE based paint



PRODUCT OVERVIEW

New and maintenance work Residential and commercial sites
Recommended for marine and industrial environments

BENEFITS

High alkali and acid resistance
Excellent adhesion
Microporous
French classification D2 - Standard P84.403
European classification G3E3S1V2W1A0C0 - Standard EN 1062-1

TECHNICAL SPECIFICATIONS

FINISH	flat
DENSITY	1.56 +/- 0,05 Kg/l
SOLIDS BY	Weight : 73 +/- 2% Volume : 50 +/- 2%
VOC	EU limit value for this product . (cat. A/c): 430 g/l (2010). This product contains max 430 g/IVOC
FLASH POINT	23°C to 55°C
GLOSS LEVEL AT	5 % 85°
AFNOR CLASSIFICATION NFT 36 005	Rating Family I Class 7b1
COLOURS	White and pastel tints from the Peintures Maestria
CONTAINER SIZE	2.5L - 15L

SURFACE PREPARATION | APPLICATION

As stated by DTU 59.1, all surfaces must be clean, dry and free of dirt.
Old glossy painted surfaces must be previously sanded or washed with an appropriate cleaner and then rinsed with water.
In the presence of contaminants such as mildew, molds or bacteria, apply an anti-fungal treatment named IKAR AM.
If required an high-pressure cleaning must be carried out, followed by the application of an anti-fungal treatment named IKAR AM.
Do not apply on wood and metal. These recommendations do not override a specific description of the substrate.

Application conditions	DTU 59.1
Application equipment	Brush : Dilution 0 to 3 % Facade roller : Dilution 0 to 3 %.Airless spray-gun : Dilution 0 to 3 %.
Practical coverage	6 to 12 m²/l per coat depending on surface texture.
Thinner / Clean-up solvent	White spirit
Drying time (20°C -65% RH)	Dust free : 1 h Dry : 10 h Recoat : 24 h



PRESTOLITE

SYSTEM RECOMMENDATIONS

Substrate	concrete, cement, hydraulic binder-based coating, previously painted surfaces in good condition
Primer coat	Apply 1 coat of PRESTOLITE
Top coat	Apply 1 or 2 coats of PRESTOLITE

SAFETY MEASURES

Storage	Can be kept for 1 year in unopened original container. Protect from freezing and high temperatures.
Précaution d emploi	Shake or stir before use. Use in well-ventilated areas. Keep out of reach of children. For personal protection, refer to the Safety Data Sheet (SDS).
Transport	Not subject to ADR regulations (European Agreement concerning the International Carriage of Dangerous Goods by Road).
Gestion des déchets	Close the container tightly after use. Do not dispose of residues in the sewer or with household waste. Please take your empty container to an approved collection center. Contact local authorities for information on disposal and collection procedures.